

HC-TS5500N2P-A



Product Features

- ≥ 5MP 20fps/4MP real-time image, high resolution, true color
- ≥ AHD / TVI / CVI standard and lossless video output
- ≥ Up to 1500 TVL resolution
- ≥ CMOS progressive scan, perfectly capture the moving object
- ≥ Support OSD menu
- ≥ High speed, long distance and real time transmission
- ≥ Auto color to B / W at low illumination
- ≥ Support ICR switch, true day / night
- ≥ 20m IR night view distance
- ≥ IP67 ingress protection
- ≥ Support coaxial audio transmission
- ≥ Support COC



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

| | |
|--------------------|---|
| Image Sensor | 1 / 2.5 "CMOS |
| Resolution | 5MP |
| Image Size | 2560 x 1936 |
| Video Output | AHD/TVI/CVI |
| Image System | PAL/NTSC |
| Electronic Shutter | Auto |
| IR Distance | 20m |
| Frame Rate | 5MP@20fps/4MP@30fps |
| Min. illumination | Color: 0.01lux@F1.2, AGC ON; B/W: 0 lux with IR |
| Lens | 3.6 mm |
| Audio | 1CH Built-in Mic |
| Lens Mount | M12 |
| S / N Ratio | ≥52dB (AGC OFF) |
| Ingress Protection | IP67 |

FUNCTIONS

| | |
|--------------------------|-------------------|
| Function Control | OSD (COC Control) |
| Day & Night | ICR |
| Digital WDR | 120dB |
| Digital DNR | 2D DNR |
| Global Exposure | Supported |
| Central Exposure | No |
| AGC | Supported |
| Auto White Balance | Supported |
| BLC | Supported |
| Front Light Compensation | No |
| Sharpness | Supported |
| Contrast | Supported |
| Smart IR | No |



Image Setting

Yes

Defect Correction

Auto

Language

English

Angle Adjustment

Pan: 0°~360° ; Tilt: 0°~75°; Rotation: 0°~360°

OTHERS

Power Supply

DC 12V (± 15%)

Power Consumption

IR Off : < 1W; IR On : < 3W

Working Environment

-10°C ~ 40° C, 10% ~ 90% (relative humidity)

Dimensions (mm)

162.1x 74.8 x 73.8



An ISO 9001:2008 Certified Company